ULTRA COMPACT LIGHTWEIGHT GRAB 'N' GO RESCUE / HAUL SYSTEM







Contact Capital Safety for more information on DBI-SALA's Rollgliss® Technical Rescue Range, or visit www.rollgliss.capitalsafety.com.au. Alternatively scan the QR Code above with your smart phones QR scanner/reader. QR readers are available for free from your mobiles app store.



ULTRA COMPACT LIGHTWEIGHT GRAB 'N' GO RESCUE / HAUL SYSTEM

DBI-SALA offers a selection of pre-assembled rescue/haul kits through its Rollgliss® Technical Rescue Range designed for rescue, work and industrial access to suit a variety of applications and emergency scenarios.

RESCUEMATE™ MICRO HAUL KIT



8701100 | Micro Haul Kit, 2m System

The Rollgliss® RescueMate™ Micro Haul Kit is specifically designed for emergency pick-offs and rescue rigging when compact gear is required or preferred.

The leightweight kit comes pre-rigged and is ready to go straight from the bag for fast and efficient deployment in a matter of seconds. Simply attach to an anchor and go. Complete with all the necessary components to provide a 6:1 mechanical advantage the Micro Haul Kit is ideal for a variety of rescue/haul operations.

The Rollgliss® RescueMate™ Micro Haul Kit is certified as a system as provided by the manufacturer.

FEATURES

- 6:1 mechanical advantage kit available in a variety of system lengths, ideal for self rescue, hauling loads and transfers
- Ultra compact and durable design allows you to easily carry it with you through any terrain
- Allows an injured person to be lifted for connection to the rescuer's systems and allow safe descent to the ground
- Built-in rope guides prevent overlapping, twisting and steadies the load during use.
- Twisted head unit for improved rope clearance
- Progress capture head ensures a positive lock on the haul line during raising operations
- Available in numerous system lengths to accommodate a variety of drops

RescueMate™ Micro Haul Kits Include:



Mini Hand Ascender

Triple Sheave Pulley

Triple Sheave Progress Capture Head

Kit Bag



Screw Gate Karahine

Ouick Linl

Kernmantle Rope

Specifications:										
Part Number	Ref #	Mechanical Advantage	Rope Length	Rope Size	Working Length	Weight# (approx.)	Height OD* (approx.)	Width OD* (approx.)	Minimum Breaking Strength at Cam	Working Load Limit
8701100	RMMICHK	6:1	14m	8mm	2m	2.10kg	360mm	160mm	800kg	300kg
8701101	RMMICHK	6:1	21m	8mm	3m	2.50kg	360mm	160mm	800kg	300kg
8701102	RMMICHK	6:1	28m	8mm	4m	2.85kg	360mm	160mm	800kg	300kg
8701103	RMMICHK	6:1	35m	8mm	5m	2.60kg	360mm	160mm	800kg	300kg

*OD = Outside Dimension of kit bag packed with contents. #= Weight of complete kit

Standards: CE 2056, NFPA 1983, EN 1496, EN 567, EN 12278. Compatibility: DBI-SALA RescueMateTM Micro Haul Kits are designed for use with all Capital Safety approved components and systems, or as recommended by a competent person. Special Instructions/Conditions of Use: Reading user instruction manual prior to use is essential. All users must be trained and assessed as competent prior to use.



Capital Safety - Australia & New Zealand

Australia: 1800 245 002 | New Zealand: 0800 212 505

www.capitalsafety.com.au sales@capitalsafety.com.au





