

Roze Grab

GUARDIAN
FALL PROTECTION

Part #	Description
01500	Trailing Rope Grab w/18" Extension Lanyard
01503	Trailing Rope Grab w/3' Shock Absorbing Extension Lanyard
01505	Trailing Rope Grab (No Extension)
01506	Removable Rope Positioning Device (No Extension)
01507	Trailing Rope Grab w/18" Shock Absorbing Extension Lanyard
01508	Rope Grab (No Extension)
01509	Stainless Steel Rope Grab (No Extension)
01511	Stainless Steel Trailing Rope Grab

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Custom configurations not available. Not repairable. Contact customer service for details.

Roze Grabs are suitable for the following applications:



Personal Fall Arrest: Rope Grab may be used to support a MAXIMUM 1 Personal Fall Arrest System (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6'. Maximum distance between harness D-ring and fall arrester is 36". Applicable D-ring: Dorsal.



Restraint: Rope Grab may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-310 lbs.



Use of equipment in unintended applications may result in serious injury or death. Maximum 1 attachment per connection point.

Materials: galvanized steel, stainless steel, polyester, and nylon.

Compatible with vertical lifelines with diameters from 1/2" - 5/8".

MAXIMUM 1 user per Rope Grab.



01500



01503



01505



01506



01507



01508



01509



01511