

Angel Anchor

Part #: 00260

Compliant with all applicable EN 795-2012 regulations.

Custom configurations not available. Not repairable.
Contact customer service for details.

Angel Anchor is suitable for the following applications:



Personal Fall Arrest: Angel Anchors may be used to support a MAXIMUM 1 Personal Fall Arrest System (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use. Applicable D-ring: Dorsal.



Restraint: Angel Anchors may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-220 lbs.



WARNING Use of equipment in unintended applications may result in serious injury or death. Maximum 1 attachment per connection point.

Materials: galvanized steel.

Angel Anchor dimensions/footprint:
Length: 78.2". Width: 60.5". Height: 8.1".

Angel Anchor weight: 690 lbs.

MAXIMUM 1 user per Angel Anchor.

Compatible for use on surfaces with pitches up to 5 degrees.

ALWAYS place anchor on pitch opposite work surface, and a MINIMUM 10' from the ridge and all leading edges.

Angel Anchor may be used as standalone anchor point, or in combination with compatible self-retracting lifeline (SRL) and swivel-top attachment (part # 00380). SRL and swivel-top attachment not included.

Angel Anchor may be used in combination with a compatible horizontal lifeline (HLL) system for use in Restraint applications ONLY. Maximum 2 workers per Angel Anchor HLL system.

Angel Anchor must only be used on compatible substrates. Refer to product instructions.

Angel Anchor must be installed and used under the supervision of the jobsite Competent Person. Competent Person must ensure all applicable workers are sufficiently trained in the installation and use of the Angel Anchor.

GUARDIAN

FALL PROTECTION

