





# SPECIFICATIONS

LINER MATERIALS	13g Salt and Pepper HDPE A4 Basetek Liner
<b>COATING MATERIALS</b>	Gray Polyurethane
WRIST DESIGN	Continuous Knit
SIZES	XS-XXL

PACKAGING									
CASE SIZE	XS	S	М	L	XL	XXL			
PER CARTON	12DZ	12DZ	12DZ	12DZ	12DZ	12DZ			
<b>CASE WEIGHT</b>	24.03/lbs	24.69/lbs	26.23/lbs	27.77/lbs	30.97/lbs	33.28/lbs			
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue			
ORIGIN	PRC								

## **PERFORMANCE LEVEL**

EN388: 4X41D							
ABRASION	0	1	2	3	4	5	Х
СИТ	0	1	2	3	4	5	х
TEAR	0	1	2	3	4	5	Х
PUNCTURE	0		2	3	4	5	Х
CUT TDM TEST	А	В	С	D	E	F	

#### 02-028 SPECIFICATION SHEET

# **ATTRIBUTES:**

### LINER

3

ANS

3

PUN

EN388

4X41D

( E 🗐

13g Salt and Pepper HDPE A4 Basetek Liner

COATING Gray Polyurethane Palm Coating

# **FEATURES:**

· Positive Grip in Dry and Light Oil Environments

### **APPLICATIONS:**

- Automotive Manufacturing
- Metal Stamping
- Steel Handling
- Construction
- Recycling

Armor Guys reference number: 02-028

## **CATEGORY:**

#### Basetek

**CARE INSTRUCTIONS:** 

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)



This product can expose you to N,N-Dimethylformamidewhich is known to the State of California to cause cancer. For more information go to www.P65warnings.ca.gov