

Instructions > PMI Bar Tender



WARNING

- SPECIAL TRAINING AND KNOWLEDGE ARE REQUIRED TO USE THIS PRODUCT.
- YOU MUST THOROUGHLY READ AND UNDERSTAND ALL MANUFACTURERS INSTRUCTIONS BEFORE USE.
- USE AND INSPECT THIS PRODUCT ONLY IN ACCORDANCE WITH THE MANUFACTURERS INSTRUCTIONS.
- YOU CAN CONTACT THE MANUFACTURER AT 1-706-764-1437 FOR IMPORTANT SAFETY INFORMATION.

MAINTENANCE AND CARE

Inspect the Bar-Tender periodically to check for excessive wear of the hook and loop closure and of the webbing and quick release buckle. When necessary, wash the Bar- Tender in clear water or with a mild soap, such as PMI Rope Soap. Rinse thoroughly and air dry. Store in a clean, dry place out of direct sunlight. Like all synthetic fibers, the material used to make the Bar-Tender should be protected from exposure to harsh chemicals that may cause damage.

REMOVAL FROM SERVICE

Your PMI Bar-Tender should be removed from service when it shows significant wear or has visible damage. An experienced person should be able to replace the hook and loop tape or make other repairs to the Bar-Tender if it becomes too worn.

This PMI Bar-Tender is intended to be used as a storage pouch for a brake bar rack, to reduce clutter and minimize jingling of the brake bars when the rack is being transported.

SG51167

Weight: 1.5 oz (42 g)

INSTRUCTIONS

Full Size Rack

Open the quick release buckle on the strap and open the hook and loop closure on the side of the Bar-Tender. Insert the top of the rack into the Bar-Tender, collecting the bars together at that end. If you have a hyper-bar on your rack, turn the wide side of the hyper bar toward the hook and loop closure on the Bar-Tender. Close the hook and loop closure around the bars. Although the hook and loop closure may not completely enclose a hyper bar, the Bar-Tender will still be effective in it's purpose. Pull the strap between the legs of the rack, clip the quick release buckle and cinch the strap.

Mini Rack

Open the quick release buckle on the strap. Insert your mini rack into the Bar-Tender. Pass the strap and buckle between the legs of your mini rack, clip the quick release buckle and cinch the strap tight.

ADDITIONAL INFORMATION

For additional information about this or other PMI products, contact us.

Pigeon Mountain Industries, Inc.

PO Box 803

LaFayette, GA 30728

PIGEON MOUNT

Toll Free: 888.764.1437 Phone: 706.764.1437

Fax: 800.952.3747 or 706.764.1531 n b

Email: info@pmirope.com
Web: www.pmirope.com

PMI LIMITED WARRANT

PMI products are warranted to the original retail purchaser to be free from defect in material and workmanship for a period of one year. PMI will repair or replace the item without charge provided inspection at our factory discloses no misuse or alteration, which, in our judgment, has affected the condition or functioning of the product. All implied warranties imposed by law in connection with the sale of PMI products are also limited in duration to a period of one year. PMI expressly excludes and shall not be liable for any consequential damages arising out of any breach of the express or implied warranties on sales of PMI products. Because of the high risks involved in high angle rope work such as, but not limited to, rescue, rope access, caving, rappelling, rock climbing and mountaineering, no further warranties exist or are implied by PMI. Regulations issued under the Magnuson-Moss Warranty Act require us to include the following statement: some states do not allow limitations on how long an implied warranty lasts nor the excluding or limitation of incidental or consequential damages, so the above limitations may not apply to you.