

SERIES 5

FULL-BODY HARNESS

TECHNICAL DATA & SELL SHEET - ISSUE 1

CAPTIVATED CHEST STRAP

Prevents improper adjustment and accidental slippage.

RUBBER WEB ENDS

Folded over and protects against damage.

LANYARD KEEPERS

Safely store unused lanyard leg.

RUBBER WEB KEEPERS

Retains excess webbing.

CAM BUCKLE TORSO ADJUSTER

Advanced adjustment for superior comfort and safety.

HEAVY-DUTY WAIST PAD

Ergonomic padding & sturdy support for tools.

LEG PADDING

Alleviates tension & provides comfort.



UPGRADED SHOULDER PADDING

Superior comfort & durability.

SRL CONNECTOR LOOP

Easily connect SRLs while keeping D-ring free.

RUBBER IMPACT INDICATORS

Supremely durable, load-indicating tags.

RETRACTABLE LABEL COVER

Label slides in and out of protective label cover with ease.

TRAUMA RELIEF STRAPS

Reduce the effects of suspension trauma in the event of a fall.



Webbing: Polyester

D-Rings: Galvanized Steel

Buckles: Galvanized Steel

Capacity: 130-420 Lbs

MULTIPLE BUCKLE CONFIGURATIONS AVAILABLE

FOR MORE INFO, PLEASE CALL **1.800.466.6385** OR VISIT **GUARDIANFALL.COM**

SERIES 5

FULL-BODY HARNESS

TECHNICAL DATA & SELL SHEET - ISSUE 1

Applications



Personal Fall Arrest: A Series 5 Harness may be used in Personal Fall Arrest applications as a component of a Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', unless used in combination with equipment explicitly certified for extended free fall. Applicable D-ring: Dorsal.



Restraint: A Series 5 Harness may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, & Shoulder.



Work Positioning: A Series 5 Harness, configured with side D-rings, may be used in Work Positioning applications. Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. Maximum allowable free fall is 2'. Applicable D-rings: Side.



Rescue/Confined Space: A Series 5 Harness may be used in Rescue/Confined Space applications. Rescue systems function to safely recover a worker from a confined location or after exposed to a fall. There are various configurations of Rescue systems depending on the type of rescue. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. No free fall is permitted. Applicable D-rings: Dorsal, Chest, & Shoulder.

Standards

- OSHA 1910
- OSHA 1926 Subpart M
- ANSI Z359.11-2014
- ANSI A10.32-2012 regulations



Made from some or all of the following materials: polyester and galvanized steel.

Always follow all manufacturer's instructions for proper adornment and use. Some steps of adorning a harness may require assistance from another person.

Upon completely adorning a harness, Guardian Fall Protection recommends that another person, with knowledge of the safe and correct use of the harness, inspect to ensure the harness is being worn correctly.

FOR MORE INFO, PLEASE CALL **1.800.466.6385** OR VISIT **GUARDIANFALL.COM**