

ROLLGLISS™ RESCUEMATE™
AUTO LOCK HAUL KIT

COMPACT GRAB 'N' GO AUTO LOCK RESCUE/ HAUL SYSTEM.



Scan this QR code
with your smart
phone to learn more
about Rollgliss™
Technical Rescue.



THE ULTIMATE IN FALL PROTECTION

PRODUCT SHEET

ROLLGLISS™ RESCUEMATE™ AUTO LOCK HAUL KIT

COMPACT GRAB 'N' GO AUTO LOCK RESCUE/HAUL SYSTEM

Our Rollgliss™ Technical Rescue Range offers pre-assembled rescue/haul kits for rescue, work and industrial access to suit a variety of applications and emergency pick-offs.

RESCUEMATE™ AUTO LOCK HAUL KIT



8704104 | 4:1, 33 ft (10 m) System



8705104 | 6:1, 33 ft (10 m) System

FEATURES

- Available in 4:1 or 6:1 mechanical advantage kits in a variety of system lengths, ideal for a wide variety of rescue and hauling operations
- Provides a safe and easy to operate hauling system, allowing rescue personnel and general workers easy access to difficult areas
- Unique Auto lock mechanism has the ability to be released without a separate tag line, provides ascent/descent control anywhere on the rope
- Built-in rope guides prevent overlapping, twisting and steadies the load during use
- Twisted head unit for improved rope clearance with ascent/descent control
- Progress capture head ensures a positive lock on the haul line during raising operations
- Available in numerous system lengths to accommodate a variety of drops
- Pre-rigged and ready to go straight from the bag
- NFPA 1983 certified as a system as provided by the manufacturer

RescueMate™ Auto Lock Haul Kits Include:

4:1 Manual Lock Haul Kits:



2 x Screw Gate Carabiners 1 x Triple Sheave Progress Capture Head 1 x Double Sheave Pulley Kit Bag Kernmantle Rope

6:1 Auto Lock Haul Kits:



2 x Screw Gate Carabiners 1 x Triple Sheave Progress Capture Head 1 x Triple Sheave Pulley Kit Bag Kernmantle Rope

Specifications:

Part Number	Mechanical Advantage	Rope Length	Rope Size	Working Length	Weight* (approx.)	Height OD** (approx.)	Width OD* (approx.)	Minimum Breaking Strength at Cam	Safe Working Load
8704104	4:1	164 ft (50 m)	3/8" (11 mm)	33 ft (10 m)	17.5 lbs. (7.95 kg)	28" (700 mm)	8" (200 mm)	1,755 lbs. (7.8 kN)	660 lbs. (300 kg)
8704105	4:1	246 ft (75 m)	3/8" (11 mm)	50 ft (15 m)	29 lbs. (13.20 kg)	29" (730 mm)	9" (230 mm)	1,755 lbs. (7.8 kN)	660 lbs. (300 kg)
8705104	6:1	230 ft (70 m)	3/8" (11 mm)	33 ft (10 m)	24 lbs. (11.00 kg)	29" (730 mm)	9" (230 mm)	1,755 lbs. (7.8 kN)	660 lbs. (300 kg)
8705105	6:1	328 ft (100 m)	3/8" (11 mm)	46 ft (14 m)	13.5 lbs. (6.12 kg)	29" (730 mm)	9" (230 mm)	1,755 lbs. (7.8 kN)	660 lbs. (300 kg)

*OD = Outside Dimension of kit bag packed with contents. **= Weight of complete kit.

Standards: CE 2056, NFPA 1983, EN 1496, EN 567, EN 12278. Compatibility: DBI-SALA RescueMate™ Auto Lock Haul Kits are designed for use with all Capital Safety approved components and systems, or as recommended by a competent person.

Special Instructions/Conditions of Use: Reading user instruction manual prior to use is essential. All users must be trained and assessed as competent prior to use.

Capital Safety - USA: 800 328 6146

Canada: 800 387 7484 | Latin America: +1 651 385 4301

Asia: +65 65587758 | Germany: +49 7195 977 11 14

New Zealand: +64 0800 212 505 | Australia: +61 1800 245 002

Europe, Middle East, Africa: +33 (0)4 97 1000 10

Northern Europe: +44 (0)1527 548000

www.capitalsafety.com info@capitalsafety.com

